

HSF



ROHS

SPECIFICATION

Current Rating: 3 Amp
Insulation Resistance: 1000M ohms min
Contact Resistance: 20M ohms max
Dielectric Withstanding: AC500V
Operating Temperature: -65 °C to +125 °C
Contact Material: Brass
Insulator Material: PA6T,UL 94V-0 Black

Ordering Code:

PHEM08 - X - X - D - A - D1 - D2 - W - X - X - X - X
① ② ③ ④ ⑤ ⑥ ⑦ ⑧ ⑨

① Series No:

② No. of Contacts
02 To 80

③ Contact Plating:

G0:Gold flash S0:Selective
G1:3U" Gold S1:Selective 3u"
G2:5u" Gold S2:Selective 5u"
G3:10u" Gold S3:Selective 10u"
G4:15u" Gold S4:Selective 15u"
G5:30u" Gold S5:Selective 30u"
SN:Tin

④ Connector Type
D: Dual

⑤ Pin Length:
A:0600=6.00mm
D1:0155=1.55mm
D2:0060=0.60mm
W:0760=7.60mm
Please mark the desired
length in the A/D1/D2/W

⑥ Insulator Material
A:PBT
B:PA6T
C:LCP
D:PA46
E:PA9T

⑦ Packing:
A:Tray
B:Bag
T:Tube
U:Tube+CAP
R:Tape&Reel
W:Tape&Reel+CAP

⑧ With locating pegs option
A:Type A without pegs
B:Type B with pegs

⑨ Plastic High
H1:1.70mm
H2:2.54mm
H3:2.00mm
H4:1.50mm

TYPE A

TYPE B

PCB LAYOUT


Standard IE P/N :

PHEM08-10-G0-D-0600-0155-0060-0760-B-B-A-H1

A	D1	D2	W	Unless Otherwise specified tolerance	
6.0	1.55	0.60	7.60	X. ±0.35	X.XX: ±0.20
				X.X: ±0.25	X.XXX: ±0.15

Optional

SCALE:	UNIT:
As Shown	mm
DRAW	DATE
Wu Feng Rong	01/05/2016
CHECK	DATE
BobYang	01/05/2016



ANTENK ELECTRONICS CO.,LTD
Http://www.antenk.com
E-mail:sales@antenk.com

TITLE: 2.54mm Pin Header DualRow Straight
SMT Type Plane Bending

DRAWING NO: PHEM08-XXD-0600-0155-0060-0760-XXXX

PRODUCT NO: PHEM08-XXD-0600-0155-0060-0760-XXXX

Changei W=5.00 TO 7.60

ADD H4=1.5MM

Increase packing method and material

DESCRIPTION

DATE